

Table 1
Design Standards for Street Classifications

Street Element (feet) ¹ Functional Classification	Cross-Section Width	Travel Lanes	Center Turn Lanes	Bike Lanes	Sidewalks	On-Street Parking	Planting Strip	Shoulder
Minor Arterial	46-86'	Two @ 11-14'	Optional 14'	6' on both sides	6-8' on both sides	None	Optional 4-8'	None
Major Collector	36-80'	Two @ 11-14' If no bike lane, min 12' travel lane with sharrow ³	None ²	Required if no sharrow, ³ 6' on both sides	6' on both sides	Optional 8' on both sides	Optional 4-6'	If no parking or bike lanes, outside travel lane of 15'
Minor Collector	34-76'	Two @ 11-14' If no bike lane, min 12' travel lane with sharrow ³	None ²	Optional 6' on both sides	5-6' on both sides	Optional 8' on both sides	Optional 4'	If no parking or bike lanes, outside travel lane of 15'
Local Street	34-40'	Travel-way of 24-30' (total)	None	None	If no shoulder, 5' on both sides	Allowed in travel-way	None	Optional 5'

¹ Range of widths listed represent minimum and maximum acceptable widths.

² Unless required by a specific development

³ A sharrow is a pavement marking that indicates a travel lane is a shared bicycle and vehicle facility.